

## **BL420 SERIES** Baylight Available in 30, 60, & 80 Watt



### **Key Features**

The high-powered LED chip offers superior brightness, proven to eliminate safety concerns while providing exceptional light quality for highly productive environments. Use the 80 watt Bay Series LED to replace your old 250W lighting system. This 1-for-1 250W HID equivalent eliminates your relamping cost, reduces energy consumption by up to 70% and delivers more light, more efficiently.

## **Recommended Use**


Make industrial walkways safer, low mounting situations brighter, storage areas luminous and give low clearance situations as much room as possible with the BL420. Suitable for wet and dry locations, the BL420 series will illuminate your showroom, warehouse or industrial walkway beautifully.

Certified for general or hazardous locations.

## Advantages

- Production & quality control completed at Lumisave's local manufacturing facilities.

- Every chip tested on site.
- Multi Chip has 80,000 Hours+ lifespan and produces 100 lumens per watt
- Hazardous Location Certified
- Rugged, weather-proof design
- 5 Year replacement warranty
- Up to 70% energy savings




Lumisave Industrial LED Technologies Ltd. | www.lumisave.com 1001 Great Street, Prince George, BC, V2N 2K8 | Ph: 250-563-7283 | Toll Free: 1-855-563-7284 | Fax: 250-563-7289 | #1-1715 27th Avenue NE, Calgary, AB, T2E 7E1 | Ph: 403-276-3944 | Toll Free: 1-855-563-7284 | Fax: 403-735-3347 |




# **BL420 SERIES**

#### DIMENSIONS - all measurements in millimetres

A		В					
		RS	RD	RA	RN		
30W	150	140	250	250	55		
60W	230	140	250	250	55		
80W	230	140	250	250	55		
С		420	500	500	120		







### **Specifications**

MULTI Voltage	120-277V**
Power Factor	≤ 95%
LED Luminous Efficiency	100 (Lm/W)
Colour Temperature	5000K**
Colour Rendering Index	Ra > 70
Maximum Intensity Angle	$\geq$ 120 Degree
Work Temperature	-40°C to + 40°C
Work Humidity	10% to 95% RH
Chip Life Expectancy	80,000 Hours (LM70)
Fixture	Black Aluminum Alloy Housing
Lens	Tempered Glass**
Weight	4.5 - 6.8 kg
Protection	IP65
Approved	Class 1 Div II, Class 2 Div II, RoHS, CE, cETLus.
	Tested to CSA Standard
**! umicovo oon produco odditio	nal specifications. Available upon request

#### Sample Order Number: LS-BL420-30W-DC-RS-W7T-MH-H1

LS-BL420										
SERIES	WATTAGE	VOL	TAGE	LENS	REFLECTOR	CA	BLEWHIP	MOUNTING		HazLoc
LS-BL420	30W	MV	120-277V DC	CLEAR DOME <b>RS</b>	SHALLOWALUMINUM	W7	7'WHIP	MH MALE THREAD HOOK	HO	NON HAZARDOUS
	60W	347	347v* <b>DF</b>	FROSTED DOME <b>RD</b>	DEEP ALUMINUM	W(X)	CUSTOM WHIP	MP 1/2" PENDANT MOUNT	H1	HAZARDOUS
	80W	480	480v* LG	glass dome <b>RA</b>	LEXAN REFLECTOR	W(X)P	PLUG END*	MW WALL MOUNT		
				RC	CUTOFF REFLECTOR	W(X)T	TWIST LOCK*			
				RN	NO REFLECTOR	W(X)F	INLINE FUSING*			

\*Call Lumisave for more details about custom orders 1-855-563-7284