

## **Key Features**

The high-powered LED chip offers superior brightness, proven to eliminate safety concerns while providing exceptional light quality for highly productive environments. It can be mounted from above or by using a wall mount. It is useful for high humidity workplaces as well as frigid and hostile **locations** 

## **Recommended Use**

Use the 150/200 watt Bay Series LED to replace your old 400 watt lighting system. This 1-for-1 HID equivalent eliminates your relamping cost, reduces energy consumption by up to 60%, and delivers more light more efficiently. Use in warehouses, manufacturing plants, where long life source is required, high mounting height, chemical plants, or storage buildings.

# **Advantages**

- Production & quality control completed at Lumisave's local manufacturing facilities.
- Every chip tested on site.
- Multi Chip has 80,000 Hours+ lifespan and produces 100 lumens per watt - Hazardous Location Certified
- Rugged, weather-proof design
- 5 Year replacement warranty
- Up to 70% energy savings






# **BL520 SERIES**

#### **DIMENSIONS - all measurements in millimetres**

A		В								
		RS	RD	RA	RC	RN	DGW			
100W	150	140	260	260	165	55	65			
150W	180	140	260	260	165	55	65			
200W	250	140	260	260	165	55	65			
С		500	420	420	360	280	280			





### **Specifications**

MULTI Voltage	120 -277V** or 347-480V**
Power Factor	≤ 95%
LED Luminous Efficiency	100 (Lm/W)
Colour Temperature	5000K**
Colour Rendering Index	Ra > 70
Maximum Intensity Angle	≥ 160 Degree
Work Temperature	-40°C to + 40°C
Work Humidity	10% to 95% RH
Chip Life Expectancy	80,000 Hours (LM70)
Fixture	Black Aluminum Alloy Housing
Lens	Tempered Glass**
Weight	9-12.2 kg
Protection	IP65, Wet Location
Approved	Class 1 Div II, Class 2 Div II, RoHS, CE, cETLus.
	Tested to CSA and UL Standards
**Lumisave can produce addition	nal specifications. Available upon request

Sample Order Number: LS-BL520-100W-HV-DG-RS-W7-MH-H1

LS-BL520													
SERIES	WATTAGE		VOLTAGE		LENS		REFLECTOR	CA	ABLE WHIP		MOUNTING		HazLoc
LS-BL520	100W	MV	120-277V	DG	GLASS DOME	RS	SHALLOWALUMINUM	W7	7'WHIP	MH	MALE THREAD HOOK	Н0	NON HAZARDOUS
	150W	H۷	347-480V*	DGW	GLASS DOME	RD	DEEP ALUMINUM	W(X)	CUSTOM WHIP	MP	1/2" PENDANT MOUNT	H1	HAZARDOUS
	200W			C	/w WIREGAURD	RA	LEXAN REFLECTOR			MW	WALL MOUNT		
						RC	CUTOFF REFLECTOR			UAP	Universal Mount		
						RN	NO REFLECTOR						