

# **BL550-G2 SERIES**

# 100W | 200W | 360W

### Industrial LED Bay Light

UL1598 rated bay light designed for Heavy Industrial environments High Lumen Output Optimized Accessories Designed for industrial applications







# **Key Applications**

- Heavy Industrial Applications
- Industrial Walkways and Catwalks
- Storage Areas
- Operational Lighting
- Task Lighting
- Oil & Gas
- Mining
- Forestry
- General Location Areas

#### **Compliances**

UL/cUL Listed to:

• UL 1598 Suitable for Wet Locations

IP66



# **Specifications**

Voltage	108-380VAC		
Power Factor	<95%		
Efficancy	140 Lumens/Watt		
Lumen Output	LS-BL550-G2-100W: 14,000 LM LS-BL550-G2-200W: 28,000 LM LS-BL550-G2-360W: 50,400 LM		
Colour Temp.	5000K Standard   Custom CCT Available		
CRI	RA>70		
Frequency	50-60Hz		
LED Diodes	Lumileds 3030		
Power Supply	Sosen		
Optics	120°   90°   60°		
Operating Temp	-40°C to +40°C		
Weight	LS-BL550-G2-100W: 8 LBS LS-BL550-G2-200W: 14 LBS LS-BL550-G2-360W: 20 LBS		
Connections	1/2" NPT		
Mounting	Hook Mount (Standard) Pendant Mount Standard Bracket Mount (Wall and Surface)		
Warranty	5 Year Standard		

For IES files, see website or contact Lumisave







# **BL550-G2 SERIES**

Industrial LED Bay Light

# Lumisave INDUSTRIAL LIGHTING

#### **Dimensions**





А	В	С	
100W 340mm	183mm	288mm	
200W 400mm	188mm	288mm	
360W 460mm	200mm	288mm	

Example: LS-BL550-G2-100W-MV-LW-MH

Model	Wattage	Voltage	Lens	Mounting
LS-BL550-G2	100W	UNV	DC	МН
	200W		DF	MP
	360W		DG	MS
				UMS
				UAP

Wattage	Volatge	e	Lens		Mount	ing
100W	UNV	108-380Vac	LW	Wide Lens (120°)	МН	Hook Mount
200W			LM	Medium Lens (90°)	MP	Pendant Mount
360W			LN	Narrow Lens (60°)	MS	Standard Mount (Bracket)
					UMS	Universal Mounting System
					UAP	Universal Adapter Plate

#### Notes

- 1 Special project pricing and support available upon inquiry
- 2 Product customization available upon consultation

# **Mounting Accessories**

Universal Mounting System (LS-UMS) - Wall & Stanchion Mounting Applications (Available for 100W Model Only)

• 1/2" NPT threaded connections | 1-1/2" NPT threaded Stanchion Connection

Universal Adapter Plate (LS-UAP) - Retrofit Adapter Plate for Crouse Hinds VMV Series Products

• Available for Appleton, Dialux and Holophane Products upon inquiry

