




XBL SERIES

60W | 80W | 150W | 200W | 240W
Hazardous & General Rated LED Bay Light

UL844 hazardous rated bay light designed for
Heavy Industrial environments
High Lumen Output
Optimized Retrofit Accessories Designed for
industrial applications



Key Applications

- Heavy Industrial Applications
- Industrial Walkways and Catwalks
- Platform Lighting
- Storage Areas
- Operational Lighting
- Task Lighting
- Oil & Gas
- Mining
- Forestry
- General Location Areas
- Explosion Proof Areas

Compliances

UL/cUL Listed to:

- UL 1598A Suitable for Wet/Marine Locations
- CLASS I, DIV. I, GROUPS C,D
- DIV. 2 GROUPS A,B,C,D - T4 CLASS II
- DIV. I, GROUPS E,F,G / DIV. 2 GROUPS E,F,G - T4 CLASS III - T4

IP66



Specifications

Voltage	120-277V or 347-480V	
Power Factor	>95%	
Efficacy	140 Lumens/Watt	
Lumen Output	LS-XBL-60W: 8,400 LS-XBL-80W: 11,200 LS-XBL-150W: 21,000	LS-XBL-200W: 28,000 LS-XBL-240W: 33,600
Colour Temp.	5000K Standard Custom CCT Available	
CRI	RA>70	
Frequency	50-60Hz	
LED Diodes	Lumileds 3030	
Power Supply	Meanwell Series	
Optics	120°	
Operating Temp	-40°C to +60°C	
Weight	LS-XBL-60W: 31 LBS LS-XBL-80W: 31 LBS LS-XBL-150W: 38 LBS	LS-XBL-200W: 46 LBS LS-XBL-240W: 46 LBS
Connections	3/4" NPT	
Mounting	Standard Bracket (Standard) Pendant Mount Wall Mount Stanchion Mount	
Warranty	5 Year Standard	

For IES files, see website or contact Lumisave




XBL SERIES


Hazardous Rated LED Bay Light




Dimensions



60W|80W



150W



200W|240W

Ordering Information

Example: LS-XBL-60W-MV-50-BS-12D

Model	Wattage	Voltage	Colour Temp	Mounting	Optics
LS-XBL	60W	MV	50	BS	12D
	80W	HV	CTM	MP	90D
	150W			MW	60D
	200W			MS	40D
	240W				

Wattage	Volatge	Colour Temp	Mounting	Optics
60W	MV 120-277Vac	50 5000K	BS Standard Bracket	12D 120°
80W	HV 277-480Vac	CTM 3000-6000K	MP Pendant Mount	90D 90°
150W			MW Wall Mount	60D 60°
200W			MS Stanchion Mount	40D 40°
240W				

Notes

- 1 Special project pricing and support available upon inquiry
- 2 Product customization available upon consultation